

2.

Declaration of Performance no.A0002

AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP – Rev. 00

Date 19/04/2019

Page 1 of 3

 Univocal product-type identification code: PIASTRA-FINO (600) 	١.	Univocal	product-type	identification	code: PIAS	TRA-FINO	(600-800)
---	----	----------	--------------	----------------	------------	----------	-----------

- Type, lot, series no. or any other element that enables the construction product to be identified pursuant to article 11, paragraph 4: **PIASTRA/FINO**
 - 4. Intended use(s) of the construction product according to the relative harmonised technical specification, as stated by the manufacturer: Heat emitting radiators designed for permanent installation in heating systems of residential buildings, fed from a remote source with hot water or steam at a temperature < 120 °C. (EN 442-1 December 2014, EN 442-2 December 2014)
 - 5. Name, registered trade name or registered trademark and address of the manufacturer pursuant to article 11, paragraph 5: Al-Tech S.r.l. Via E. Ferrari, 1 62017 Porto Recanati (MC) ITALIA
 - **6.** If applicable, name and address of mandatary whose mandate includes the assignments as per article 12, paragraph 2: **N.A.**
 - 7. System(s) for the assessment and verification of constancy of performance of the construction product, as per annex V: system 1.
 - 8. In a declaration of performance concerning a construction product that comes under the scope of a harmonised standard:

Notified Testing Laboratory: Politecnico di Milano – Energy Department (Notified body number: 1695)

(name and identification number of notified body, if applicable)

has performed **type tests (standard UNI EN 442-1)** according to system 1. (description of third party assignments as per annex V)

and has issued:

- Determination of the thermal output of a heating body (Test report ENE/MRT.RES.17011 del 21/03/2017)
- Pressure tightness tests (Test report ENE/MRT.RAP.17011/P del 21/03/2017, ENE/MRT.RAP.17042/P 25/01/2017

(constancy of performance certificate, plant production control conformity certificate, test/design reports – as applicable)

Notified Testing Laboratory: AQM S.r.I. (LAB N° 0095)

(name and identification number of organisation notified, if applicable)

has performed **type tests (standard UNI EN 442-1)** according to system **1.** (description of third party assignments as per annex V)

and has issued:

- Adherence test and Corrosion test in salt mist. (Test report 2019-0533/PC8 del 27/02/19)
 (constancy of performance certificate, plant production control conformity certificate, test/design reports as applicable)
- 9. In a declaration of performance concerning a construction product for which a European technical assessment has been released:



NI A

10.

Declaration of Performance no.A0002

AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP - Rev. 00

Date 19/04/2019

Page 2 of 3

(name and identification number of technical assessment body, if applicable)
has released
(reference number of European technical assessment)
based on
(reference number of European assessment document)
performed
and has issued
(constancy of performance certificate, plant production control conformity certificate, test/design reports - as applicable)
Performance declared
Notes to table:

- 1. Column 1 contains the list of the basic properties as defined in the harmonised technical specifications for the use(s) specified in § 3 above;
- 2. For each property listed in column 1 and conforming to the requirements as per article 6, this column gives the performance declared, expressed in terms of level, class, or through a description, in relation to the corresponding basic properties. If no performance has been declared, the column shows "NPD" (No Performance Determined):
- 3. For each basic property listed in column 1, column 3 gives:
 - A reference, with relative date, to the corresponding harmonised standard, and, if applicable, the reference number of the specific technical documentation, or that of the appropriate technical documentation used;

or

b. A reference, with relative date, to the corresponding European assessment document, if available, and the reference number of the European technical assessment used;



Declaration of Performance no.A0002

AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP - Rev. 00

Date 19/04/2019

Page 3 of 3

	The second of th		
Reaction to fire	A1	Tests on organic part of any paint or surface treatment substance to verify whether it is <1 % by mass. (Clause 5.2, standard EN 442-1:2014)	
Release of hazardous substances	None	Clause 5.3, standard EN 442- 1:2014	
Surface temperature	120° C maximum and corresponding to water supply temperature	EN 442-1:2014	
Maximum operating pressure	10 bar	EN 442-1:2014	
Pressure tightness (leak test)	13 bar	Clause 5.4, standard EN 442- 1:2014	
Pressure tightness (resistance test)	16.90 bar	Clause 5.6, standard EN 442- 1:2014	
Rated thermal output ΔT 50 K	See Table 1	Clause 5.8, standard EN 442- 1:2014	
Rated thermal output ΔT 30 K	See Table 1	Clause 5.8, standard EN 442- 1:2014	
Thermal power in different operating conditions (Characteristic equation)	Φ = Km x ΔT ⁿ	Clause 5.8, standard EN 442- 1:2014	
Coefficient Km	See Table 1	Clause 5.8, standard EN 442- 1:2014	
Coefficient n	See Table 1	Clause 5.8, standard EN 442- 1:2014	
Durability (impact resistance lightweight)	Level 0	Clause 5.9, standard EN 442- 1:2014	
Durability (corrosion test)	No corrosions after 100 h in salt mist	Clause 5.9, standard EN 442- 1:2014	

If a specific technical document has been used, pursuant to art. 37 or art. 38, the requirements met by the product:

11. The performance of the product as per §§ 1 & 2 above conforms to the performance declared as per § 9.



Declaration of Performance no.A0002

AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP – Rev. 00

Date 19/04/2019

Page 4 of 3

Modell	Rated thermal output ΔT 50 K	Rated thermal output ΔT 30 K	Coefficient Km	Coefficient n
PIASTRA/FINO 600	64,4 Watt/elemento	33,1 Watt/elemento	3,87046	1,30751
PIASTRA/FINO 1800	176,8 Watt/elemento	90,6 Watt/elemento	10,56449	1,30876

This declaration of performance is released under the sole responsibility of the manufacturer as per § 4 above.

Signed in the name and on behalf of:

Chiara Foglieni

Legal representative

Porto Recanati (MC - Italy)

04/03/20

FIRMA DIGITALE