

AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP - Rev. 00			
Date	06/05/13		
Page 1 of 3			

1.	Univocal product-typ	e identification code	: PIANO MOVE V	ERTICALE (cor	nplete rang	ae)

- 2. Type, lot, series no. or any other element that enables the construction product to be identified pursuant to article 11, paragraph 4: **PIANO MOVE VERTICALE**
- 3. Intended use(s) of the construction product according to the relative harmonised technical specification, as stated by the manufacturer: Heat emitting radiators designed for permanent installation in heating systems of residential buildings, fed from a remote source with hot water or steam at a temperature < 120 °C. (EN 442-1 December 2014, EN 442-2 December 2014)
- 4. Name, registered trade name or registered trademark and address of the manufacturer pursuant to article 11, paragraph 5: Radiatori 2000 S.p.a. Via Francesca, 54/A 60, 24040 Ciserano (BG) ITALY
- 5. If applicable, name and address of mandatary whose mandate includes the assignments as per article 12, paragraph 2: **N.A.**
- 6. System(s) for the assessment and verification of constancy of performance of the construction product, as per annex V: **system 3**.
- 7. In a declaration of performance concerning a construction product that comes under the scope of a harmonised standard:

Notified Testing Laboratory: Politecnico di Milano – Energy Department (Notified body number: 1695)

(name and identification number of notified body, if applicable)

has performed **type tests (standard UNI EN 442-1)** according to system **3.** (description of third party assignments as per annex V)

and has issued:

- Determination of the thermal output of a heating body (Test report ENE/MRT.RES.17018 of 14/04/17)
- Pressure tightness tests (Test report ENE/MRT.RES.17018 of 14/04/17) (constancy of performance certificate, plant production control conformity certificate, test/design reports as applicable)

(name and identification number of organisation notified, if applicable)
(description of third party assignments as per annex V)
and has issued:
(constancy of performance certificate, plant production control conformity certificate, test/design reports – as applicable)



AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP - Rev. 00			
Date	06/05/13		

Page 2 of 3

8. In a declaration of performance concerning a construction product for which a European technical assessment has been released:

N.A. (name and identification number of technical assessment body, if applicable)
has released
(reference number of European technical assessment)
based on
(reference number of European assessment document)
performed
and has issued
(constancy of performance certificate, plant production control conformity certificate, test/design reports – as applicable)
Performance declared

#### Notes to table:

9.

- 1. Column 1 contains the list of the basic properties as defined in the harmonised technical specifications for the use(s) specified in § 3 above;
- 2. For each property listed in column 1 and conforming to the requirements as per article 6, this column gives the performance declared, expressed in terms of level, class, or through a description, in relation to the corresponding basic properties. If no performance has been declared, the column shows "NPD" (No Performance Determined):
- 3. For each basic property listed in column 1, column 3 gives:
  - a. A reference, with relative date, to the corresponding harmonised standard, and, if applicable, the reference number of the specific technical documentation, or that of the appropriate technical documentation used:

or

b. A reference, with relative date, to the corresponding European assessment document, if available, and the reference number of the European technical assessment used;



AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP - Rev. 00

Date 06/05/13

Page 3 of 3

Basic properties	Performance	Harmonised technical spec.
(see note 1)	(see note 2)	(see note 3)
Reaction to fire	A1	Tests on organic part of any paint or surface treatment substance to verify whether it is <1 % by mass. (Clause 5.2, standard EN 442-1:2014)
Release of hazardous substances	None	Clause 5.3, standard EN 442- 1:2014
Surface temperature	120° C maximum and corresponding to water supply temperature	EN 442-1:2014
Maximum operating pressure	16 bar	EN 442-1:2014
Pressure tightness (leak test)	20,8 bar	Clause 5.4, standard EN 442- 1:2014
Pressure tightness (resistance test)	27 bar	Clause 5.6, standard EN 442- 1:2014
Rated thermal output ΔT 50 K	See Table 1	Clause 5.8, standard EN 442- 1:2014
Rated thermal output ΔT 30 K	See Table 1	Clause 5.8, standard EN 442- 1:2014
Thermal power in different operating conditions (Characteristic equation)	$\Phi = \text{Km x } \Delta T^n$	Clause 5.8, standard EN 442- 1:2014
Coefficient Km	See Table 1	Clause 5.8, standard EN 442- 1:2014
Coefficient n	See Table 1	Clause 5.8, standard EN 442- 1:2014
Durability (impact resistance lightweight)	Level 0	Clause 5.9, standard EN 442- 1:2014
Durability (corrosion test)	No corrosions after 100 h in salt mist	Clause 5.9, standard EN 442- 1:2014

product:	cal document has bee	en used, pursuant to a	art. 37 or art. 38, the	requirements met by	ine

10. The performance of the product as per §§ 1 & 2 above conforms to the performance declared as per § 9.



AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP - Rev. 00 06/05/13 Date

Page 4 of 3

### TABLE 1 (tecnica data)

Modell	Rated thermal output ΔT 50 K	Rated thermal output ΔT 30 K	Coefficient Km	Coefficient n
H 600	109,5 Watt/element	57,9 Watt/element	0,829	1,248
H 700	123,8 Watt/element	65,5 Watt/element	0,939	1,247
H 800	137,8 Watt/element	72,9 Watt/element	1,047	1,247
H 900	151,5 Watt/element	80,1 Watt/element	1,154	1,246
H 1000	165,1 Watt/element	87,1 Watt/element	1,239	1,250
H 1100	178,4 Watt/element	94,0 Watt/element	1,321	1,253
H 1200	191,7 Watt/element	100,8 Watt/element	1,399	1,257
H 1300	204,8 Watt/element	107,5 Watt/element	1,474	1,261
H 1400	217,8 Watt/element	114,4 Watt/element	1,569	1,261
H 1500	230,8 Watt/element	121,2 Watt/element	1,663	1,260
H 1600	243,7 Watt/element	128,0 Watt/element	1,758	1,260
H 1700	256,6 Watt/element	134,8 Watt/element	1,852	1,260
H 1800	269,4 Watt/element	141,5 Watt/element	1,946	1,260
H 1900	282,2 Watt/element	148,2 Watt/element	2,040	1,260

This declaration of performance is released under the sole responsibility of the manufacturer as per § 4 above.

Signed in the name and on behalf of:

ARIANNA SCARAVAGGI

**Managing Director** (name and functions)

Ciserano (BG - Italy) 02/05/2017 (place and date of issue)

(signature)